

Computational and Experimental Comparison of CLF5605 and Roamx-0201 Martian Helicopter Rotor Airfoils

Lidia Caros*

Imperial College London, London SW7 2AZ, United Kingdom

Witold J. F. Koning†

NASA Ames Research Center, Moffett Field, California 94035

Takayuki Nagata‡

Nagoya University, Nagoya 464-8603, Japan

Keisuke Asai§

Tohoku University, Sendai 980-8579, Japan

Oliver Buxton¶

Imperial College London, London, England, United Kingdom

Natalia Perez Perez** and Ethan A. Romander††

NASA Ames Research Center, Moffett Field, California 94035

Taku Nonomura‡‡

Nagoya University, Nagoya 464-8603, Japan

Haley V. Cummings§§

NASA Ames Research Center, Moffett Field, California 94035

and

Peter Vincent¶¶

Imperial College London, London, England, United Kingdom

<https://doi.org/10.2514/1.J066610>

This study compares the performance of the CLF5605 rotor airfoil—which flew on Ingenuity—with that of a new optimized roamx-0201 airfoil designed for Martian conditions at NASA Ames Research Center. Specifically, performance is studied at a Reynolds number of 20,000 and a Mach number of 0.60 across a range of angles of attack. In this regime, flow can be highly sensitive to geometry and operating conditions, and results from computational analysis and physical testing can be strongly affected by small differences in setup. Accordingly, in order to achieve confidence in observed trends, the airfoils are studied using three independent state-of-the-art methodologies: implicit large-eddy simulations using NASA's OVERFLOW solver, direct numerical simulations using the high-order PyFR solver, and experimental testing in the Mars Wind Tunnel at Tohoku University. Across methodologies, the roamx-0201 airfoil achieves an ~19–43% improvement in lift-to-drag ratio relative to the CLF5605 airfoil. Moreover, OVERFLOW and PyFR results show that the roamx-0201 airfoil has superior stall characteristics and can achieve a maximum lift ~20% higher than the CLF5605 airfoil. The work provides a strong body of evidence to support further studies into the use of rotors based on the optimized roamx-0201 airfoil for future Mars helicopter missions.

I. Introduction

IN APRIL 2021, NASA successfully flew the Ingenuity helicopter on Mars [1], marking a significant milestone in planetary exploration. Ingenuity went on to complete a further 71 flights, unequivocally demonstrating that powered flight on the red planet was possible and paving the way for future helicopter-based exploration of Mars. Consequently, NASA has now begun scoping next-generation Martian helicopters—such as the Mars Science Helicopter [2], the Mars Sample Recovery Helicopters [3], and the Mars Chopper concept [4]—with increased range, flight duration, and payload capacity compared to Ingenuity, such that they could explore further and faster and carry scientific instruments and/or surface samples, enabling a wide range of currently intractable science and discovery missions.

A key determinant of the overall performance of a Martian helicopter is the aerodynamic efficiency of the rotor blades, which in turn depends significantly on the rotor blade airfoil profiles that are employed. The atmospheric conditions on Mars—and in particular the low atmospheric density—mean rotors must operate in a low-Reynolds-number compressible regime for which terrestrial rotor blades have not been designed [5]. This has led to interest in a range of novel airfoil concepts [6,7], including corrugated airfoils [8,9] inspired by dragonfly wing profiles [10], polygonal airfoils, including triangular airfoils [11–15], and thin cambered plates

Received 14 November 2025; accepted for publication 7 July 2026; published online 21 September 2026. Copyright © 2026 by the authors. Published by the American Institute of Aeronautics and Astronautics, Inc., with permission. All requests for copying and permission to reprint should be submitted to CCC at www.copyright.com; employ the eISSN 1533-385X to initiate your request. See also AIAA Rights and Permissions <https://aiaa.org/publications/publish-with-aiaa/rights-and-permissions/>.

*Research Associate, Department of Aeronautics; lidia.caros-roca19@alumni.imperial.ac.uk (Corresponding Author).

†ROAMX Computational Lead, Analytical Mechanics Associates; witold.koning@nasa.gov.

‡Assistant Professor, Department of Aerospace Engineering; also Analytical Mechanics Associates, Hampton, Virginia; takayuki.nagata@mae.nagoya-u.ac.jp.

§Professor Emeritus, Department of Aerospace Engineering.

¶Professor, Department of Aeronautics; o.buxton@imperial.ac.uk.

**ROAMX Experimental Lead, Analytical Mechanics Associates; nataliaperez@alumni.stanford.edu.

††Aerospace Engineer, Aeromechanics Branch; ethan.romander@nasa.gov.

‡‡Professor, Department of Aerospace Engineering; also Analytical Mechanics Associates, Hampton, Virginia; nonomura@nagoya-u.jp.

§§ROAMX Principal Investigator, Aeromechanics Branch; haley.cummings@nasa.gov.

¶¶Professor, Department of Aeronautics; p.vincent@imperial.ac.uk.




Fig. 1 CLF5605 (a) and roamx-0201 (b) airfoils.

[8,16]. One such design is the optimized roamx-0201 airfoil [8,17], developed for Martian conditions of $Re = 20,000$ and $Ma = 0.60$ using the Evolutionary Algorithm for Iterative Studies of Aeromechanics (ELISA) [8], as part of the Rotor Advancement for Mars Exploration (ROAMX) project [18].

This study compares the aerodynamic performance of the CLF5605 rotor airfoil shown in Fig. 1a [19,20]—which flew on Ingenuity from 2021 to 2024—with that of the optimized roamx-0201 airfoil shown in Fig. 1b [8,21], at a chord-based $Re = 20,000$ and $Ma = 0.60$ across a range of angles of attack α . In this regime, flow can be highly sensitive to geometry and operating conditions, and results from both computational analysis and physical testing can be strongly affected by small differences in setup. Accordingly, in order to achieve confidence in observed performance trends, the CLF5605 and roamx-0201 airfoils are studied using three independent state-of-the-art methodologies: implicit large-eddy simulations (ILESs) using NASA's OVERFLOW solver [22,23], direct numerical simulations (DNS) using the high-order GPU-accelerated PyFR solver [24,25], and experimental testing in the Mars Wind Tunnel (MWT) at Tohoku University [26]. Section II details the computational methodologies, Sec. III details the experimental methodologies, Sec. IV presents the results and discussion, and, finally, Sec. VI draws conclusions.

II. Computational Methodologies

A. Solvers and Numerical Methods

OVERFLOW [22,23] is a compressible Navier–Stokes solver based on the finite difference method. For the present study, OVERFLOW 2.3d was used. Inviscid fluxes were computed using an improved Harten, Lax, and van Leer flux scheme (HLLE++) with a fifth-order WENOM upwind reconstruction [27], and viscous fluxes were computed using second-order central differencing. Time was advanced using a second-order backward differencing scheme (BDF2) with the dual time-stepping approach as described in [28,29]. ILESs with OVERFLOW were undertaken using CPU nodes on the Pleiades supercomputer provided by the NASA High-End Computing Program through the NASA Advanced Supercomputing Division at Ames Research Center.

PyFR [24,25] is an open-source computational fluid dynamics solver based on the high-order Flux Reconstruction approach of Huynh [30]. For the present study, PyFR v1.15.0 and v2.0.3 were used. Fourth-order polynomials were used to represent the solution within each element of the mesh, thus nominally achieving fifth-order accuracy in space. A Rusanov Riemann solver was used to calculate the interelement inviscid fluxes, the local discontinuous Galerkin approach was used to calculate the interelement viscous fluxes, an explicit RK45 scheme [31] was employed to advance the solution in time, anti-aliasing was employed to stabilize the simulations, and all

runs were performed using double-precision arithmetic. DNSs with PyFR were undertaken using Nvidia P100 GPUs on Piz Daint and Nvidia GH200 GPUs on Alps at the Swiss National Supercomputing Centre (CSCS) under project s1271.

Both OVERFLOW and PyFR have previously been validated in a low-Reynolds-number compressible regime and used to simulate flow over Martian rotor blade airfoil concepts [7,13–16,32].

B. Governing Equations

OVERFLOW and PyFR were used to solve the compressible Navier–Stokes equations for a calorically perfect gas with constant viscosity, which can be written in three dimensions as

$$\frac{\partial \mathbf{u}}{\partial t} + \nabla \cdot \mathbf{f} = 0 \quad (1)$$

where $\mathbf{u} = \mathbf{u}(\mathbf{x}, t) = (\rho, \rho v_x, \rho v_y, \rho v_z, E)$ is the solution with ρ the fluid density; $\mathbf{v} = (v_x, v_y, v_z)$ is the fluid velocity; E is the total energy per unit volume; and $\mathbf{f} = \mathbf{f}(\mathbf{u}, \nabla \mathbf{u}) = \mathbf{f}^i - \mathbf{f}^v$ is the flux, with $\mathbf{f}^i$ the inviscid flux given by

$$\mathbf{f}^i = \begin{pmatrix} \rho v_x & \rho v_y & \rho v_z \\ \rho v_x^2 + p & \rho v_x v_y & \rho v_x v_z \\ \rho v_x v_y & \rho v_y^2 + p & \rho v_y v_z \\ \rho v_x v_z & \rho v_y v_z & \rho v_z^2 + p \\ v_x(E + p) & v_y(E + p) & v_z(E + p) \end{pmatrix} \quad (2)$$

where p is the pressure, which for a calorically perfect gas is given by

$$p = (\gamma - 1) \left(E - \frac{1}{2} \rho \|\mathbf{v}\|^2 \right) \quad (3)$$

with $\gamma = c_p/c_v$, where c_p and c_v are specific heat capacities at constant pressure and volume, respectively, and $\mathbf{f}^v$ is the viscous flux given by

$$\mathbf{f}^v = \begin{pmatrix} 0 & 0 & 0 \\ \mathcal{T}_{xx} & \mathcal{T}_{yx} & \mathcal{T}_{zx} \\ \mathcal{T}_{xy} & \mathcal{T}_{yy} & \mathcal{T}_{zy} \\ \mathcal{T}_{xz} & \mathcal{T}_{yz} & \mathcal{T}_{zz} \\ v_i \mathcal{T}_{ix} + \kappa \partial_x T & v_i \mathcal{T}_{iy} + \kappa \partial_y T & v_i \mathcal{T}_{iz} + \kappa \partial_z T \end{pmatrix} \quad (4)$$

where the stress-energy tensor is given by

$$\mathcal{T}_{ij} = \mu(\partial_i v_j + \partial_j v_i) - \frac{2}{3} \mu \delta_{ij} \nabla \cdot \mathbf{v} \quad (5)$$

where μ is the dynamic viscosity, $\kappa = \mu c_p / Pr$ (with Pr the Prandtl number), and T is the temperature, which for a calorically perfect gas is given by

$$T = \frac{1}{c_v} \frac{1}{\gamma - 1} \frac{p}{\rho} \quad (6)$$

In the current study, values of $\gamma = 1.4$ and $Pr = 0.71$ are used, corresponding to the properties of air at ambient temperature. While values of $\gamma = 1.29$ and $Pr = 1.18$ are more representative of the Martian atmosphere, the chosen values were selected to match the experimental conditions in the Tohoku University MWT.

C. Two-Dimensional Simulations

1. Domain

Both OVERFLOW and PyFR were used to undertake two-dimensional (2D) simulations of flow over the CLF5605 and roamx-0201 airfoils. Figures 2 and 3 show 2D domains for OVERFLOW and PyFR simulations, respectively. In all cases, each airfoil is defined to have a chord of $c = 1.0$.

For OVERFLOW simulations, α was changed by varying the freestream inflow angle. The origin in the streamwise-vertical xy -plane was located at the airfoil quarter-chord position. The dimensions of the computational domain for OVERFLOW simulations were $x \in [-205, 205]$ in the streamwise direction and $y \in [-205, 205]$ in the vertical direction. For PyFR simulations, α was changed by rotating each airfoil about its trailing edge. The origin in the streamwise-vertical xy -plane was located at the leading edge of each airfoil when $\alpha = 0$ deg. The dimensions of the computational domain were $x \in [-20, 46]$ in the streamwise direction and $y \in [-20, 20]$ in the vertical direction.




Fig. 2 Views of domain and mesh in the streamwise-vertical xy -plane used for 2D simulations with OVERFLOW for the CLF5605 (a) and roamx-0201 (b) airfoils.




Fig. 3 Views of domain and mesh in the streamwise-vertical xy -plane used for 2D and 3D-SP simulations with PyFR for the CLF5605 (a) and roamx-0201 (b) airfoils when $\alpha = 6$ deg.

2. Meshes

For OVERFLOW simulations, overset structured meshes were used, consisting of near-body and off-body components. Specifically, a near-body O-mesh was overset with Cartesian blocks in the wake, extending a distance of 5 chord lengths downstream, and a coarse Cartesian background mesh, following the approach detailed in Koning et al. [33]. Figure 2 shows meshes used for the CLF5605 and roamx-0201 airfoils, with each having $\sim 3 \times 10^5$ mesh points.

For PyFR simulations, meshes were composed of structured and unstructured regions. Specifically, structured quadrilateral boundary-layer meshes were located adjacent to the airfoil upper and lower surfaces, extending a distance of 0.1 chord lengths normally from the surface into the domain. Around the leading and trailing edges, a refined unstructured mesh was located adjacent to the surface, extending a distance of 0.1 chord lengths normally from the surface into the domain. Refined regions were extended a distance of 0.5 chord lengths normally into the domain on the upper surface to provide enough resolution for the separated flow at the highest angles of attack. An unstructured refined region was also located in the wake region, extending a distance of 6 chord lengths downstream of the airfoil. The remainder of the domain was then tessellated with an unstructured mix of quadrilaterals and triangles. Figure 3 shows meshes used for the CLF5605 and roamx-0201 airfoils at $\alpha = 6$ deg, which

each had $\sim 1\text{--}2 \times 10^4$ elements and $\sim 4\text{--}5 \times 10^5$ degrees of freedom per equation in total when fourth-order solution polynomials were used to represent the solution within each element.

Mesh independence was demonstrated for both OVERFLOW and PyFR (see Appendix A).

3. Boundary Conditions

For both OVERFLOW and PyFR, a characteristic boundary condition was applied at the inflow, outflow, bottom, and top planes in order to achieve freestream flow in the x -direction at the inflow plane with a chord-based $Re = 20,000$ and $Ma = 0.60$ for all simulations. Also, an impermeable no-slip adiabatic boundary condition was prescribed at the airfoil surface. For the PyFR simulations, a sponge region was applied adjacent to the outlet plane in order to help damp outgoing wake disturbances and suppress reflections.

4. Startup Process and Data Extraction

Both OVERFLOW and PyFR simulations were initiated at $t = 0$ with spatially uniform freestream conditions throughout the domain. Following Bergmann et al. [34], simulations were then advanced for a period t_i to remove initial transients and then for a further t_e ,

henceforth referred to as the data extraction period, during which data were extracted for analysis. For OVERFLOW, $t_i = 620t_c$ and $t_e = 60t_c$, where for the first $480t_c$ of t_i , a first-order convergence criterion was applied at each time step to accelerate the passing of the transient, and during the data extraction period, a time step of $\Delta t = 2.5 \times 10^{-3}t_c$ was employed. For PyFR, $t_i = 100t_c$ and $t_e = 100t_c$, and during the data extraction period a time step of $\Delta t = 2 \times 10^{-5}t_c$ was employed. In all cases, $t_c = c/v_\infty$, where v_∞ is the freestream velocity magnitude at the inflow plane.

D. Three-Dimensional Spanwise Periodic Simulations

1. Domain

Both OVERFLOW and PyFR were used to undertake three-dimensional spanwise periodic (3D-SP) simulations of flow around each airfoil profile. Domains for each simulation were obtained by extruding the respective 2D domain a distance of 0.5 chord lengths in the spanwise direction. Spanwise domain size independence was demonstrated for both OVERFLOW and PyFR (see Appendix B).

2. Meshes

For OVERFLOW, 3D-SP meshes were obtained by extruding 2D meshes, similar to those used for each respective 2D simulation, in the spanwise direction. These 3D-SP meshes had 62.8×10^6 mesh points for the CLF5605 and 62.4×10^6 mesh points for the roamx-0201 airfoil.

For PyFR, 3D-SP meshes were obtained by extruding the respective 2D meshes in the spanwise direction, generating hexahedra and triangular prisms throughout the domain. These 3D-SP meshes had $\sim 0.8\text{--}1 \times 10^6$ elements and $\sim 0.1 \times 10^9$ degrees of freedom per equation in total when fourth-order solution polynomials were used to represent the solution within each element. For the $\alpha = 6$ deg case, it was verified a posteriori that $3.5\eta > \Delta$ in the wake for 6 chord lengths downstream of the airfoil (see Appendix C), where

$$\Delta = \frac{\sqrt[3]{V}}{P+1} \quad (7)$$

is an estimate of the local solution point spacing, with V the local element volume and P the polynomial order used to represent the solution within each element of the mesh, and

$$\eta = \left(\frac{\nu^3}{\epsilon}\right)^{1/4} \quad (8)$$

is the Kolmogorov length scale, with ν the kinematic viscosity and

$$\epsilon = 2\nu S_{ij}S_{ij} \quad (9)$$

is the dissipation rate, where S_{ij} is the fluctuating rate-of-strain tensor. This is consistent with ranges reported in prior DNS studies [35,36].

3. Boundary Conditions

For both OVERFLOW and PyFR, a characteristic boundary condition was applied at the inflow, outflow, bottom, and top planes in order to achieve freestream flow in the x -direction at the inflow plane with a chord-based $Re = 20,000$ and $Ma = 0.60$ for all simulations. Also, an impermeable no-slip adiabatic boundary condition was prescribed at the airfoil surface, and periodic boundary conditions were applied in the spanwise direction.

4. Startup Process and Data Extraction

Both OVERFLOW and PyFR simulations were initiated and advanced in an analogous way to the 2D simulations. For OVERFLOW, $t_i = 532.5t_c$ and $t_e = 60t_c$, where for the first $480t_c$ of t_i , a first-order convergence criterion was applied at each time step to accelerate the passing of the transient, and during the data extraction period, a time step of $\Delta t = 2.5 \times 10^{-3}t_c$ was employed. For PyFR,

$t_i = 90t_c$ and $t_e = 60t_c$, where for the first $40t_c$ of t_i , first-order polynomials were used to represent the solution within each element of the mesh, and for the next $40t_c$, third-order polynomials were used, in order to accelerate the passing of the transient, and during the data extraction period, a time step of $\Delta t = 2 \times 10^{-5}t_c$ was employed.

E. Virtual Wind Tunnel Simulations

1. Domain

PyFR was used to undertake virtual wind tunnel (VWT) simulations of flow around roamx-0201 at two angles of attack, $\alpha = 4.5$ deg and $\alpha = 6$ deg, in the entire working section of the MWT, thus accounting for blockage effects and the interaction of the side-wall boundary layer with the extruded airfoil. As per the 2D and 3D-SP simulations, the airfoil was defined to have a chord of $c = 1.0$. The origin in the streamwise-vertical xy -plane was located at the leading edge of each airfoil when $\alpha = 0$ deg. When changing the angle of attack, the airfoil was rotated about a point at 25% chord to agree with the experimental setup. The dimensions of the computational domain were $x \in [-3.75, 4.25]$ in the streamwise direction, $y \in [-1.496, 1.504]$ in the vertical direction at the inlet, and $z \in [0, 2]$ in the spanwise direction, with the top and bottom walls inclined at an angle of 1.3 deg to the streamwise direction. This configuration matches the working section of the Tohoku University MWT, in which the experiments were undertaken.

2. Meshes

The virtual wind tunnel meshes were obtained by extruding meshes analogous to the 2D streamwise-vertical xy -plane meshes in the spanwise z direction. The streamwise-vertical xy -plane meshes were composed of structured and unstructured regions. Specifically, structured quadrilateral boundary-layer meshes were located adjacent to the airfoil upper and lower surfaces, extending a distance of 0.1 chord lengths normally from the surface into the domain. Around the leading and trailing edges, a refined unstructured mesh was located adjacent to the surface, extending a distance of 0.1 chord lengths normally from the surface into the domain. Refined regions were extended a distance of 0.5 chord lengths normally into the domain on the upper surface to provide enough resolution for the separated flow at the highest angles of attack. Structured quadrilateral meshes were also located adjacent to the top and bottom walls, extending a distance of 0.3 chord lengths normally into the domain. Mesh cells adjacent to the wind tunnel walls are sized targeting $\Delta < \delta_\nu$, where $\delta_\nu \sim \sqrt{\nu x/U_\infty}$ is an estimate of the viscous diffusion length scale based on the Blasius flat-plate scaling. The remainder of the streamwise-vertical xy -plane meshes are tessellated with an unstructured mix of quadrilaterals and triangles. Extrusion of the 2D meshes in the spanwise z direction generates hexahedra and triangular prisms throughout the domain. Figure 4 shows the external surface of the mesh for roamx-0201 at $\alpha = 6$ deg. Meshes had $\sim 5 \times 10^6$ elements and $\sim 625 \times 10^6$ degrees of freedom per equation in total when fourth-order solution polynomials were used to represent the solution within each element.

3. Boundary Conditions

Neither the inlet turbulence intensity nor the inlet boundary-layer profile at the entrance of the Mars Wind Tunnel test section was measured during the experimental campaign. Consequently, in the absence of this information, the inflow for the VWT simulations was specified as steady and uniform, without synthetic turbulence injection or prescribed boundary-layer profiles. Specifically, a fixed uniform total pressure and total temperature were applied at the inflow plane, and a characteristic boundary condition was applied at the outflow plane in order to achieve freestream flow in the x -direction at the inflow plane with a chord-based $Re = 20,000$ and $Ma = 0.60$. Also, an impermeable no-slip adiabatic boundary condition was prescribed at the airfoil surface and the wind tunnel walls.




Fig. 4 View of the computational mesh used for the virtual wind tunnel (VWT) with PyFR for roamx-0201 at $\alpha = 6$ deg. The origin in the streamwise-vertical xy -plane is located at the leading edge of the airfoil when $\alpha = 0$ deg.

4. Startup Process and Data Extraction

Simulations were initiated and advanced in an analogous way to the 3D-SP PyFR simulations. Specifically, $t_i = 80t_c$ and $t_e = 20t_c$, where for the first $40t_c$ of t_i first-order polynomials were used to represent the solution within each element of the mesh and for the next $20t_c$ third-order polynomials were used, in order to accelerate the passing of the transient, and during the data extraction period a time step of $\Delta t = 2 \times 10^{-5}t_c$ was employed.

F. Extracted Quantities

Instantaneous lift and drag coefficients were extracted, defined as

$$C_L = \frac{F_L}{q_\infty}, \quad C_D = \frac{F_D}{q_\infty} \quad (10)$$

respectively, where F_L and F_D are the sum of the instantaneous pressure and viscous forces on the airfoil per unit area in the y and x directions, respectively, and q_∞ is obtained via

$$q_\infty = \frac{1}{2}\rho_\infty v_\infty^2 \quad (11)$$

where ρ_∞ is the freestream density. From these, time-averaged lift and drag coefficients $\bar{C}_L$ and $\bar{C}_D$ could be obtained by time-averaging C_L and C_D , respectively, over the data extraction period. Additionally, time-averaged pressure coefficients were extracted, defined as

$$\bar{C}_p = \frac{\bar{p} - p_\infty}{q_\infty} \quad (12)$$

where $\bar{p}$ is obtained by time-averaging p over the data extraction period. Finally, instantaneous snapshots of density gradient magnitude $|\nabla\rho|$ in the xy -plane and Q -criterion isosurfaces in the volume were extracted.

III. Experimental Methodology

A. Mars Wind Tunnel

The Tohoku University MWT [26,37] was used for the experimental measurements. This wind tunnel is housed in a vacuum chamber, as shown in Fig. 5, and hence experiments can be conducted under low-pressure conditions. The wind tunnel is driven by an ejector system [38] due to the inability of a fan to generate high-subsonic flow under low-pressure conditions. The ejector system is located downstream of the test section and induces a flow in the wind tunnel via supersonic jets. The pressure in the chamber increases due to the operation of the ejector. Therefore, an appropriate amount



Fig. 5 The MWT at Tohoku University, Japan. The facility is now located at Nagoya University, Japan.

of gas is exhausted into a separately installed buffer tank, and the total pressure inside the wind tunnel can be maintained for a finite period. The amount of exhaust gas is adjusted by a proportional–integral–derivative (PID) controller butterfly valve installed in the flow path connecting the main tank and buffer tank. The test section of the wind tunnel is 100 mm wide and 150 mm high.

Various fundamental studies of low-Reynolds-number compressible flow over an airfoil [12,39,40], plate [41,42], and circular cylinder [43,44] have been conducted in the MWT. Surface flow visualization for a rotor blade, using the pressure-sensitive paint (PSP) and sublimation method, has also been conducted [45]. In addition, the experimental report and data for the CLF5605 and roamx-0201 airfoils are presented in [46].

B. CLF5605 Models

Three models of the CLF5605 profile were produced, as shown in Fig. 6. Models clf5605-us-s and clf5605-us-fp were fabricated in the United States from AISI 4130 using electrical discharge machining (EDM) and used for schlieren measurements and force and PSP measurements, respectively, and model clf5605-jp-f was fabricated in Japan from A5052 using an EDM method and used for force measurements.

C. Roamx-0201 Models

Five models of the roamx-0201 profile were produced, as shown in Fig. 7. Models roamx-0201-us-f, roamx-0201-us-pu, and roamx-0201-us-pl were fabricated in the United States from AISI 4130 using a computer numerical control (CNC) mill and were used for force measurements, upper surface PSP measurements, and lower surface PSP measurements, respectively, and models




Fig. 6 Images of CLF5605 models (scale shown in cm).




Fig. 7 Images of roamx-0201 models (scale shown in cm).

roamx-0201-jp-s and roamx-0201-jp-fpu were fabricated in Japan from A5052 using EDM and used for schlieren measurements and force and upper surface PSP measurements, respectively.

The roamx-0201-based PSP assemblies require separate models for the upper and lower sides since the mounting bracket is part of the assembly, and hence the model cannot be reversed to illuminate the lower surface. This is in contrast to CLF5605-based PSP models, which have sufficient thickness to fix the mounting bracket with screws, so it can be detached. The roamx-0201-jp-fpu model was initially only intended for force measurements but was later also used for upper surface PSP measurements.

D. Operating Conditions

The target flow condition was $Ma = 0.60$ at $Re = 20,000$, and the angle of attack was varied in the range of $-2.0 \text{ deg} \leq \alpha \leq 6.0 \text{ deg}$. Due to time constraints, schlieren visualizations and PSP measurements were conducted at fewer angles of attack than the force measurements, as shown in Table 1.

E. Instrumentation

1. Schlieren Visualization

The setup for schlieren visualization is shown in Fig. 8. The schlieren optical system uses a white LED (PFBR-600SW-LL, CCS) as a light source. A pinhole (F70, Surugaseiki) with a diameter of 2.0 mm was used, and a point light source was created. Concave mirrors with a focal length of 1500 mm were used as the

Table 1 List of experimental conditions

α, deg	Schlieren visualization	Force measurement	PSP measurement
-2.0	✓	✓	✓
0.0	✓	✓	✓
2.0	✓	✓	✓
2.5	—	✓	—
3.0	✓	✓	✓
3.5	—	✓	—
4.0	✓	✓	✓
4.5	—	✓	—
5.0	✓	✓	✓
5.5	—	✓	—
6.0	✓	✓	✓

first and second collimators, and a planoconvex lens with a focal length of 1000 mm was used as the imaging lens. The knife edge was installed horizontally, and the lower half of the light flux was cut off at the focal point of the second collimator, which visualized the density gradient field perpendicular to the freestream. The time series of schlieren images was captured by a high-speed camera (SA-X2, Photron). The exposure time and frame rate were $2.5 \mu\text{s}$ and 72,000 fps, respectively. In this experiment, parallel light was




Fig. 8 Schematic diagram of optical system used for schlieren visualization.

reflected by a plane mirror and passed through the test section due to space constraints in the laboratory. The airfoil model was mounted directly between the optical glasses of the wind tunnel side wall. The influence of noise caused by atmospheric fluctuations was reduced physically by covering the optical path with duct hoses both outside and inside the main tank.

2. Force Measurement

The lift and drag forces were measured using a three-component force balance system. This balance system consists of load cells (LC-4100-G-600 and LC-4101-K-003, A&D) for drag and lift directions and a stepping motor (PK513PA-H50S, Oriental Motor LTD) for adjusting the angle of attack. The accuracy of the stepping motor is 0.0144 deg. The zero angle of attack was determined by the inclinometer, and an airfoil mold was used for placing the inclinometer on the airfoil to ensure a reliable reference surface. The accuracy of the mold placement onto the airfoil was not quantified. However, we note that the roamx-0201-us models were slightly modified by the machining process, and thus, the mold and wing model did not fit perfectly. The accuracy of the inclinometer used to determine a 0 deg pitch angle is 0.1 deg. The rated capacities of the load cells for the drag and lift directions are 6 N and 30 N, respectively, and the accuracies are 4.0×10^{-4} N and 1.4×10^{-3} N, respectively. The measurement system samples signals from force sensors at 100 Hz and records the average value of 10 samples at 10 Hz.

3. PSP Measurement

The time-averaged measurements of the surface pressure were performed with polymer-based PSP [47]. Under low-pressure conditions, the normalized sensitivity (normalized by the ambient pressure) and time response of PSP are degraded [48–50]. Therefore, PSP specialized for low-pressure conditions must be used. The PSP used in the present study was composed of Pd(II) meso-tetra(pentafluorophenyl) porphyrin (PdTFPP) luminophore and (poly)trimethylsilylpropanoic [(poly)TMSP] polymer [51], which has high-pressure sensitivity under low-pressure conditions [52,53]. The PC-PSP binder of Sugioka et al. [54], formulated with an 85 weight percent (wt %) particle mass fraction and no luminophore, was used as the white base coat. Although polymer-based PSPs for unsteady measurement under low-pressure conditions [55] have been developed recently, the present study focused on obtaining time-averaged measurements.

Figure 9 shows a schematic diagram of the experimental PSP measurement setup. Two UV-LEDs (IL-106, Hardsoft) were used as an excitation light source, and a scientific CMOS camera (C13440-20CU, Hamamatsu Photonics) was used as a photodetector. A camera lens (Nikkor 105 mm $f/2.0$, Nikon) was used as an imaging lens with a 640 ± 50 nm band-pass filter (PB640-100, Asahi Spectra) to cut off the light other than PSP emission. Excitation of PSP and imaging of PSP emission were carried out through the




Fig. 9 Schematic diagram of an optical system used for PSP measurement.

optical windows of the main tank and the upper wall of the wind tunnel. The optical system was covered with a blackout curtain to prevent stray light. The exposure time for the imaging was set between 20 and 200 ms so that the image intensity became approximately 80% of the full-well capacity of the image sensor. Wind-on, reference, and dark images were acquired. One hundred images were then obtained for each experiment, and random noise was reduced by taking the average of each image set.

A single-point pressure measurement was simultaneously conducted by the pressure transducer (CCQ-093-5A, Kulite Semiconductor Products) and was used as a reference pressure for the PSP measurement. The signal from the pressure transducer was amplified by an amplifier (SA-570ST, TEAC) and was recorded by a data acquisition system (PCI6251, National Instruments) with a sampling frequency of 10 Hz. Although the pressure sensor is of a fast-responding type, it is not embedded in the model and is connected through a tube. The length of the tubing from the pressure tap to the sensor is around 15 cm. The measurement system samples the pressure signal at 100 Hz and records the average value of 10 samples at 10 Hz. Measurements on the upper and lower surfaces were carried out as individual experiments.

The clf5605-us-fp model uses pressure taps on the upper and lower surfaces of the airfoil for pressure calibration during PSP measurements. The pressure taps are routed out to the side of the airfoil profile to facilitate connection to the pressure gauges. The roamx-0201-us-pu and roamx-0201-us-pl models are too thin to route the pressure tap and therefore use a through-hole and a thin tube on the opposite side of the airfoil, which is used to obtain the reference pressure data. This naturally requires separate measurements for the upper and lower sides.

The Stern–Volmer coefficient and the temperature sensitivity of the PSP used in the present experiment were approximately 0.78 and $-1.41\%/K$, respectively, at the ambient pressure of 10 kPa and temperature of 283 K. A Stern–Volmer coefficient of 0.78 means a pressure sensitivity of 7.8%/kPa. Note that the PSPs using PTMSP polymers have a contamination issue due to oil mist from the vacuum pump, and the pressure sensitivity of the PSP was gradually degraded during the experimental campaign due to a decrease in the oxygen permeability caused by oil mist contamination [51,53]. The oil mist contamination gradually progressed with repeated experiments, and the lowest pressure sensitivity in the present experiment was approximately 6%/kPa. In addition, the degree of contamination caused by oil mist adhesion depends on the local flow structure, and the pressure sensitivity and its distribution slightly change run by run. Hence, calibration tests were conducted in the wind tunnel before every experiment. The PSP sensitivity is evaluated locally at each pixel by in situ calibration [56], allowing spatial variations in sensitivity to be accounted for in the pressure reconstruction. The

pressure in the main tank was changed through seven conditions, and the sensitivity distribution was obtained by correlating the pressure and intensity of the PSP emission at each pressure.

IV. Results and Discussion

A. Results

1. Lift and Drag

Figure 10 shows plots of $\bar{C}_L$ (a), $\bar{C}_D$ (b), and $\bar{C}_L/\bar{C}_D$ (c) as a function of α and $\bar{C}_L$ as a function of $\bar{C}_D$ (d) for the CLF5605 airfoil. Results are shown for 2D OVERFLOW, 2D PyFR, 3D-SP OVERFLOW, 3D-SP PyFR simulations, and MWT force balance experiments on models clf5605-us-fp and clf5605-jp-f.

Figure 11 shows plots of $\bar{C}_L$ (a), $\bar{C}_D$ (b), and $\bar{C}_L/\bar{C}_D$ (c) as a function of α and $\bar{C}_L$ as a function of $\bar{C}_D$ (d) for the roamx-0201 airfoil. Results are shown for 2D OVERFLOW, 2D PyFR, 3D-SP OVERFLOW, 3D-SP PyFR, VWT PyFR simulations, and MWT force balance experiments on models roamx-0201-us-f and roamx-0201-jp-fpu.

2. Surface Pressure

Figure 12 shows plots of $\bar{C}_p$ on both upper and lower surfaces of the CLF5605 airfoil as a function of $\tilde{x} = x/a$, where a is the x -wise distance between the leading and trailing edges of the airfoil, for various α . Results are shown for 2D OVERFLOW, 2D PyFR, 3D-SP OVERFLOW, 3D-SP PyFR simulations, and MWT PSP experiments on model clf5605-us-fp.

Figure 13 shows plots of $\bar{C}_p$ on both upper and lower surfaces of the roamx-0201 airfoil as a function of $\tilde{x} = x/a$, where a is the

x -wise distance between the leading and trailing edges of the airfoil, for various α . Results are shown for 2D OVERFLOW, 2D PyFR, 3D-SP OVERFLOW, 3D-SP PyFR, VWT PyFR simulations, and MWT PSP experiments on models roamx-0201-us-pu, roamx-0201-us-pl, and roamx-0201-jp-fpu.

Note that for 3D-SP PyFR, 3D-SP OVERFLOW, and VWT PyFR results, $\bar{C}_p$ is measured at the midspan, while for all MWT PSP experiments, $\bar{C}_p$ was obtained by taking a spanwise average with a 5% span width (approximately imaging 80 pixels) around the model centerline.

Plots of $\bar{C}_p$ at all α are included in Appendix D.

3. Schlieren, Instantaneous Density Gradient Magnitude, and Time-Averaged Line Integral Convolution

Figure 14 shows schlieren images for MWT experiments using model clf5605-us-s (top) and images of instantaneous density gradient magnitude $|\nabla\rho|$ (middle) and of time-averaged normalized velocity magnitude $|v|/v_\infty$ with superimposed Line Integral Convolutions (LICs) (bottom) for 3D-SP OVERFLOW (blue) and 3D-SP PyFR (red) for CLF5605 at $\alpha = -2, 0, 5$, and 6 deg.

Figure 15 shows schlieren images for MWT experiments using model roamx-0201-jp-s (top) and images of instantaneous density gradient magnitude $|\nabla\rho|$ (middle) and of time-averaged normalized velocity magnitude $|v|/v_\infty$ with superimposed LICs (bottom) for 3D-SP OVERFLOW (blue) and 3D-SP PyFR (red) for roamx-0201 at $\alpha = -2, 0, 5$, and 6 deg.

Note that for 3D-SP PyFR and 3D-SP OVERFLOW cases, the images of instantaneous density gradient magnitude and of time-averaged normalized velocity magnitude were extracted at




Fig. 10 Plots of time-averaged lift coefficient $\bar{C}_L$ (a), drag coefficient $\bar{C}_D$ (b), and lift-to-drag ratio $\bar{C}_L/\bar{C}_D$ (c) as a function of angle of attack α and lift coefficient $\bar{C}_L$ as a function of drag coefficient $\bar{C}_D$ (d) for the CLF5605 airfoil.




Fig. 11 Plots of time-averaged lift coefficient $\bar{C}_L$ (a), drag coefficient $\bar{C}_D$ (b), and lift-to-drag ratio $\bar{C}_L/\bar{C}_D$ (c) as a function of angle of attack α and lift coefficient $\bar{C}_L$ as a function of drag coefficient $\bar{C}_D$ (d) for the roamx-0201 airfoil.




Fig. 12 Plots of time-averaged pressure coefficient $\bar{C}_P$ as a function of $\tilde{x}$ for different angles of attack for the CLF5605 airfoil.




Fig. 13 Plots of time-averaged pressure coefficient $\bar{C}_p$ as a function of $\tilde{x}$ for different angles of attack for the roamx-0201 airfoil.

the midspan plane. Schlieren images and images of instantaneous density gradient magnitude at all α are included in Appendix E.

4. Instantaneous Q -Criterion Isosurfaces

Figure 16 shows instantaneous Q -criterion isosurfaces colored by normalized velocity magnitude $|v|/|v_\infty|$ for 3D-SP OVERFLOW (left) and 3D-SP PyFR (right) simulations of CLF5605 at various α . Note that two views are included for the $\alpha = -2$ deg case to enable visualization of flow separation on the pressure surface of the airfoil.

Figure 17 shows instantaneous Q -criterion isosurfaces colored by normalized velocity magnitude $|v|/|v_\infty|$ for 3D-SP OVERFLOW (left) and 3D-SP PyFR (right) simulations of roamx-0201 at various α . Note that two views are included for the $\alpha = -2$ deg case to enable visualization of flow separation on the pressure surface of the airfoil.

Figure 18 shows instantaneous Q -criterion isosurfaces colored by normalized velocity magnitude $|v|/|v_\infty|$ for a VWT PyFR simulation of roamx-0201 at $\alpha = 6$ deg.

B. Flow Physics

Across all methodologies, when $\alpha = -2$ deg, both CLF5605 and roamx-0201 exhibit attached flow on their upper surfaces and separation on their lower surfaces. This is apparent in the density-gradient and schlieren images in Figs. 14a and 15a, and is also apparent in the $\bar{C}_p$ distributions in Figs. 12a and 13a. For the 3D-SP OVERFLOW and PyFR simulations, the separated flow over the lower surface undergoes spanwise breakdown, resulting in near-zero lift for CLF5605 and near-zero or negative lift for roamx-0201. This breakdown is visible in the Q -criterion isosurfaces in Figs. 16 and 17.

All methodologies show linear behavior of the lift slope for a range of α , for both CLF5605 and roamx-0201 airfoils. However,

the range of α varies across methodologies and airfoils. For the CLF5605 airfoil, 2D and 3D-SP OVERFLOW and PyFR simulations show this behavior for $0 \text{ deg} \leq \alpha \leq 5 \text{ deg}$, while MWT experiments show it for all α . For the roamx-0201 airfoil, 2D and 3D-SP OVERFLOW and PyFR simulations show this behavior for $0 \text{ deg} \leq \alpha \leq 4 \text{ deg}$, MWT roamx-0201-us-f experiments for $-2 \text{ deg} \leq \alpha \leq 4 \text{ deg}$, and MWT roamx-0201-jp-fpu experiments for all α . By looking at density gradient and schlieren images in Figs. 14 and 15 and Q -criterion isosurfaces in Figs. 16 and 17, we can observe that this linear lift behavior coincides with either attached flow or spanwise-coherent separated flow. The linearity of the lift slope, for both airfoils, terminates as soon as the flow breaks down substantially in the spanwise direction.

For the CLF5605 airfoil, when $\alpha > 5 \text{ deg}$, 3D-SP OVERFLOW and PyFR simulations exhibit stall. This occurs because the laminar boundary completely separates from the suction surface, with subsequent spanwise breakdown and a recirculation region in a time-averaged sense just above the trailing edge of the suction surface. For 3D-SP OVERFLOW and PyFR simulations, this is apparent in the density-gradient and LIC images in Fig. 14d and the Q -criterion isosurfaces in Fig. 16. In contrast, the MWT experiments do not appear to exhibit stall, and the 2D OVERFLOW and PyFR simulations suppress spanwise breakdown and artificially sustain spanwise-coherent structures that lead to an increment in lift when $\alpha > 5 \text{ deg}$.

For the roamx-0201 airfoil, when $\alpha > 4 \text{ deg}$, 2D and 3D-SP OVERFLOW and PyFR simulations, VWT PyFR simulations, and MWT roamx-0201-us-fp experiments all show a lift increment. This behavior can be attributed to separation from the sharp leading edge followed by a Kelvin–Helmholtz instability and subsequent roll-up of vortices close to the upper surface of the airfoil, resulting in a recirculation region in a time-averaged sense adjacent to the front half of the upper surface that sustains suction over a significant




Fig. 14 Schlieren images for MWT experiments on clf5605-us-s (top) and images of instantaneous density gradient magnitude $|\nabla\rho|$ (middle) and of time-averaged normalized velocity magnitude $|v|/v_\infty$ with superimposed LICs (bottom) for 3D-SP OVERFLOW (blue) and 3D-SP PyFR (red) on CLF5605 for different α .

portion of the airfoil. This is particularly apparent in the density-gradient and LIC images in Figs. 15c and 15d, the schlieren image in Fig. 15d, and the $\bar{C}_p$ distributions in Figs. 13c and 13d.

C. Comparison Between Methodologies

1. Context

The objective of the current study is to compare the aerodynamic performance of the CLF5605 and roamx-0201 airfoils at a chord-based $Re = 20,000$ and $Ma = 0.60$ across a range of angles of attack α . In this regime, flow can be highly sensitive to geometry and operating conditions, and results from both computational analysis and physical testing can be strongly affected by small differences in setup. Accordingly, in order to achieve confidence in observed performance trends, we have adopted various independent state-of-the-art methodologies to analyze the flow, including 2D OVERFLOW and PyFR simulations, 3D-SP OVERFLOW and PyFR simulations, and MWT experiments. Quantitative

differences between results from the various methodologies are expected and indeed observed in this sensitive regime. They are discussed below.

2. Comparison Between OVERFLOW and PyFR

Results obtained from OVERFLOW and PyFR are similar across both 2D and 3D-SP simulations for both CLF5605 and roamx-0201 airfoils. This serves as a good cross-validation of the independent meshing and solver pipelines. Moreover, it suggests that the ILES resolution afforded by the OVERFLOW simulations is sufficient to capture the relevant flow physics.

3. Comparison Between 2D and 3D-SP

For the CLF5605 airfoil, Fig. 10 shows discrepancies between 2D and 3D-SP results in $\bar{C}_L$ for all α , with lower $\bar{C}_L$ values for 3D-SP, as well as discrepancies in $\bar{C}_D$ for $\alpha < 0$ deg, with higher $\bar{C}_D$ values for 3D-SP, and $\alpha > 3$ deg, with lower $\bar{C}_L$ values for 3D-SP. The $\bar{C}_L$




Fig. 15 Schlieren images for MWT experiments on roams-0201-jp-s (top) and images of instantaneous density gradient magnitude $|\nabla\rho|$ (middle) and of time-averaged normalized velocity magnitude $|v|/v_\infty$ with superimposed LICs (bottom) for 3D-SP OVERFLOW (blue) and 3D-SP PyFR (red) on roams-0201 for different α .

discrepancies correlate with discrepancies in $\bar{C}_p$ distributions in Fig. 12, where 3D-SP shows lower suction on the upper surface of the airfoil. These discrepancies, at the lowest and highest values of α , are caused by flow separation and subsequent spanwise breakdown of the vortices for the 3D-SP simulations, which is not possible for the 2D simulations. In particular, and notably, the 2D simulations fail to capture the stall behavior of the CLF5605 airfoil for $\alpha > 5$ deg and show, instead, an increment in lift.

For the roams-0201 airfoil, Fig. 11 only shows discrepancies between 2D and 3D-SP results in $\bar{C}_L$ and $\bar{C}_D$ for $\alpha = -2$ deg, which correlates with discrepancies in $\bar{C}_p$ distributions for this α . $\bar{C}_L$ and $\bar{C}_D$ for all other α are in good agreement. However, for $\alpha = 5$ deg and $\alpha = 6$ deg, Fig. 13 shows that $\bar{C}_p$ distributions on the suction side of the airfoil differ between 2D and 3D-SP simulations, due to flow separation and subsequent spanwise breakdown of the vortices for the 3D-SP simulations, which is not possible for the 2D simulations. This apparent discrepancy is explained by the fact that

at $\alpha = 5$ deg and $\alpha = 6$ deg the 2D simulations produce higher and lower suction regions on the airfoil that coincidentally add to the same force obtained by the 3D-SP simulations.

4. Comparison Between 3D-SP and MWT Experiments

For the CLF5605 airfoil, Fig. 10a shows that 3D-SP simulations and MWT experiments follow a similar trend for $\bar{C}_L$ when $0 \text{ deg} \leq \alpha \leq 5 \text{ deg}$ with lift increasing approximately linearly with angle of attack. However, $\bar{C}_L$ values for the MWT experiments are, in general, between 20% and 40% lower. For $\alpha = -2$ deg, $\bar{C}_L$ values are closer. For $\alpha > 5$ deg, the MWT experiments do not appear to exhibit stall behavior, which is seen in 3D-SP simulations. Figure 10b shows that 3D-SP simulations and MWT experiments follow a similar trend for $\bar{C}_D$ for all α , but with higher experimental values up to $\alpha = 3$ deg, after which they begin to overlap. When $\alpha = 0$ deg, 3D-SP simulations exhibit attached flow on their upper and lower surfaces. This is apparent in the density-gradient images




Fig. 16 Images of instantaneous Q -criterion isosurfaces $Q = 1$ colored by normalized velocity magnitude $|v|/|v_\infty|$ obtained with 3D-SP OVERFLOW (left) and 3D-SP PyFR (right) for the CLF5605 airfoil.

in Fig. 14b and the $\bar{C}_p$ distributions in Fig. 12b. However, the schlieren images from MWT experiments in Fig. 14b and the MWT $\bar{C}_p$ distributions in Fig. 12b suggest that flow separation occurs on the lower surface of the CLF5605 airfoil in the MWT when $\alpha = 0$ deg.

For the roamx-0201 airfoil, Fig. 11a shows that 3D-SP simulations and MWT experiments follow a similar trend for $\bar{C}_L$ when $0 \text{ deg} \leq \alpha \leq 4 \text{ deg}$, with lift increasing approximately linearly with angle of attack. However, $\bar{C}_L$ values for the MWT experiments are, in general, between 30% and 55% lower. For $\alpha = -2$ deg, $\bar{C}_L$ values are closer. For $\alpha > 4$ deg, 3D-SP simulations and MWT roamx-0201-us-fp experiments both capture a nonlinear increment in $\bar{C}_L$, although the increment is lower for the MWT roamx-0201-us-fp experiment. Moreover, for the MWT roamx-0201-jp-fpu experiment, no such increment occurs. Figure 11b shows that 3D-SP simulations and MWT experiments follow a similar trend for $\bar{C}_D$ for all α , but with higher experimental values up to $\alpha = 5$ deg, after which they begin to overlap. When $\alpha = 0$ deg, 3D-SP simulations exhibit attached flow on their upper and lower surfaces. This is apparent in the density-gradient images in Fig. 15b and the $\bar{C}_p$ distributions in Fig. 13b. However, the schlieren images from MWT experiments in Fig. 15b and the MWT $\bar{C}_p$ distributions in Fig. 13b

suggest that flow separation occurs on the lower surface of the roamx-0201 airfoil in the MWT when $\alpha = 0$ deg. When $\alpha = 5$ deg, 3D-SP simulations exhibit separated flow on their upper surfaces with vortex roll-up. This is apparent in the density-gradient images in Fig. 15c and the $\bar{C}_p$ distributions in Fig. 13c. However, the schlieren images from MWT experiments in Fig. 15c and the MWT roamx-0201-us-fp $\bar{C}_p$ distributions in Fig. 13c suggest that flow is only just starting to separate on the upper surface of the roamx-0201 airfoil when $\alpha = 5$ deg.

To aid understanding of discrepancies between 3D-SP simulations and MWT experiments, VWT PyFR simulations were undertaken for the roamx-0201 airfoil at $\alpha = 4.5$ deg and $\alpha = 6$ deg. These simulations model flow in the entire working section of the MWT, thus accounting for blockage effects and the interaction of the side-wall boundary layer with the extruded airfoil. Figure 18 shows an instantaneous snapshot of Q -criterion isosurfaces colored by normalized velocity magnitude $|v|/|v_\infty|$ for the $\alpha = 6$ deg VWT PyFR simulation, looking along the length of the tunnel from the entrance of the test section. Vortical structures resulting from the interaction of the side-wall boundary layer with the extruded airfoil are clearly visible. $\bar{C}_L$ values obtained from VWT PyFR shown in Fig. 11a are closer to experimental values, reducing the discrepancy




Fig. 17 Images of instantaneous Q -criterion isosurfaces $Q = 1$ colored by normalized velocity magnitude $|v|/|v_\infty|$ obtained with 3D-SP OVERFLOW (left) and 3D-SP PyFR (right) for the roamx-0201 airfoil.





Fig. 18 Instantaneous snapshot of Q -criterion isosurfaces colored by normalized velocity magnitude $|v|/|v_\infty|$ obtained with a VWT PyFR simulation for the roamx-0201 airfoil with $\alpha = 6$ deg case.


with MWT roamx-0201-us-f experiments to approximately 15–20% and the discrepancy with MWT roamx-0201-jp-fpu experiments to approximately 40%. However, $\overline{C_D}$ values from VWT PyFR shown in Fig. 11b remain similar to results from 3D-SP.

The reduction in lift for the VWT PyFR can be attributed to the interaction of the side-wall boundary layer with the extruded airfoil, which results in further spanwise breakdown and less coherent roll-up of vortices. Figure 19 shows time series of C_L for the data


extraction period, their corresponding spectra, and snapshots of instantaneous density gradient magnitude $|\nabla\rho|$ for 2D OVERFLOW and PyFR (a), midspan 3D-SP OVERFLOW and PyFR (b), and midspan VWT PyFR (c). These images illustrate how the coherence of the vortices is reduced as one moves from 2D to 3D-SP and then to VWT PyFR simulations. Specifically, the 2D simulations exhibit strong spectral peaks at $St \approx 0.1$ – 0.4 and $St \approx 1$ – 2 , which are consistent with strong coherent structures. The 3D-SP simulations show



a) 2D OVERFLOW (top) and 2D PyFR (bottom)



b) 3D-SP OVERFLOW (top) and 3D-SP PyFR (bottom)



c) VWT PyFR

Fig. 19 C_L spectra (left), C_L as a function of time over the data extraction period (middle), and images of instantaneous density gradient magnitude $|\nabla\rho|$ (right) for the 2D (a), midspan 3D-SP (b), and midspan VWT (c) simulations of the roamx-0201 airfoil at $\alpha = 6^\circ$.

a reduction in low-frequency energy and a broader spectral distribution, indicating partial breakdown of these coherent structures. Finally, the VWT PyFR simulation exhibits reduced energy across all frequencies and a shift toward higher-frequency, lower-amplitude fluctuations, indicative of even less coherent structures.

Remaining discrepancies between the VWT PyFR simulations and the MWT experiments could be caused by manufacturing tolerances for the MWT airfoil models, which had a chord two times smaller than the design chord for the actual carbon fiber ROAMX rotor blades [8]. Indeed, previous studies have shown how small geometric deviations can significantly impact flow physics, and in particular separation, in a low-Reynolds-number compressible regime [8,14–16]. To assess the extent of any geometric deviations here, MWT airfoil models were scanned a posteriori with an optical EinScan Pro 2X 2020 scanner, and profiles were extracted and compared with their respective reference airfoils. Figures 20 and 21 show the scanned model profiles and their camberlines, compared with corresponding reference airfoils and camberlines. Furthermore, thickness and camberline deviations are quantified at selected chordwise locations and presented in Tables 2 and 3 for CLF5605 models and Tables 4 and 5 for roamx-0201 models. We note that thicknesses were calculated as the vertical distance between the upper and lower airfoil surfaces.

The clf5605-us-fp and clf5605-us-s models remain relatively close to the reference geometry, with thickness deviations within approximately +10% and reductions in camberline height of up to ~20%. In contrast, the clf5605-jp-f model is generally thinner, particularly toward the trailing edge, where thickness reductions reach up to ~30%. However, the roamx-0201 models exhibit substantially larger geometric deviations. The roamx-0201-us-f and roamx-0201-us-pl configurations show pronounced increases in thickness, with deviations ranging between ~110% and ~140%,

accompanied by significant camberline variations of up to ~35%. In contrast, the roamx-0201-jp-fp model is generally thinner than the reference geometry, with thickness reductions of up to ~30%, except near the trailing edge, where it becomes locally thicker by up to ~23%. This model also exhibits camberline deviations of up to ~21%. Additionally, differences in overall chord length are observed for the roamx-0201 models. The roamx-0201-us configurations exhibit an increased chord of approximately 50.5 mm relative to the intended manufactured chord of 50 mm, whereas the roamx-0201-jp model has a reduced chord of approximately 48.4 mm.

The measured geometric deviations are substantial, particularly for the roamx-0201 models, and likely contribute to remaining discrepancies between the VWT PyFR simulations and the MWT experiments. However, additional factors may also play a role. These include uncertainty in MWT angle-of-attack calibration; possible inlet turbulence in the MWT that is not represented in the VWT PyFR simulations (indeed, modest turbulence levels can significantly affect low-Reynolds-number compressible flows [15]); and, finally, surface roughness variations (indeed, the roamx-0201-jp-s and roamx-0201-jp-fpu models have slightly rougher surfaces due to the omission of a polishing step following EDM processing).

5. Comparison Between MWT Experiments

Differences in aerodynamic forces are observed between different models of the same reference airfoil. Specifically, for the CLF5605 airfoil, clf5605-us-fp and clf5605-jp-f show differences of 10–30% in $\bar{C}_L$ and 10–20% in $\bar{C}_D$, and for the roamx-0201 airfoil, roamx-0201-us-f and roamx-0201-jp-fpu also show differences of 10–30% in $\bar{C}_L$ and 10–20% in $\bar{C}_D$. Additionally, $\bar{C}_p$ distributions for the roamx-0201 airfoil also differ when comparing roamx-0201-us-pl and roamx-0201-jp-fpu, where roamx-0201-jp-fpu does not show




Fig. 20 CLF5605 airfoil profiles (top) and their camber lines (bottom) extracted from the scanned models (dashed lines) and compared with the reference CLF5605 airfoil and camber line (solid lines). The scanned geometries were aligned by identifying the leading and trailing edges and rotating them such that both points lie on a common horizontal axis ($y = 0$). The reference airfoil geometry is scaled to a chord length of 50 mm, corresponding to the target length of the manufactured models.




Fig. 21 Roamx-0201 airfoils (top) and their camber lines (bottom) extracted from the scanned models (dashed lines) compared with the reference roamx-0201 airfoil and camber line (solid lines). The scanned geometries were aligned with the reference roamx-0201 airfoil by identifying the leading and trailing edges and rotating them such that both points lie on a common horizontal axis ($y = 0$). The reference airfoil geometry is scaled to a chord length of 50 mm, corresponding to the target length of the manufactured models.

the area of high suction, or separation bubble, in the time-averaged sense, at $\alpha = 6^\circ$ identified in the 3D-SP simulations. The aforementioned differences are likely due to uncertainty in MWT angle-of-attack calibration and/or geometric variation between models of the same reference airfoil. Geometric variations are shown in Figs. 20 and 21 and quantified in Tables 2–5.

D. Comparison Between Roamx-0201 and CLF5605

Figure 22 compares $\bar{C}_L$ versus α (top row), $\bar{C}_L/\bar{C}_D$ versus α (middle row), and $\bar{C}_L$ versus $\bar{C}_D$ polars (bottom row) for CLF5605 and roamx-0201 airfoils obtained using 3D-SP simulations and MWT experiments. Associated comparison metrics are summarized in Table 6.

Table 2 Airfoil thickness comparison at selected chord fractions

x/c	CLF5605	clf5605-us-fp		clf5605-us-s		clf5605-jp-f	
	mm	mm	Δ , %	mm	Δ , %	mm	Δ , %
0.10	2.34	2.33	−0.3	2.43	4.1	2.28	−2.4
0.25	2.45	2.57	4.6	2.65	8.1	2.51	2.2
0.50	1.77	1.87	6.1	1.92	9.0	1.77	0.2
0.75	0.88	0.92	4.8	0.95	7.9	0.80	−9.4
0.90	0.40	0.43	7.8	0.43	9.0	0.29	−28.4

Percentage differences are computed relative to the CLF5605 reference airfoil.

Table 3 Camber line height at selected chord fractions

x/c	CLF5605	clf5605-us-fp		clf5605-us-s		clf5605-jp-f	
	mm	mm	Δ , %	mm	Δ , %	mm	Δ , %
0.10	1.17	0.95	−18.5	0.99	−15.7	0.93	−20.7
0.25	1.87	1.70	−8.8	1.76	−5.7	1.77	−4.9
0.50	2.45	2.28	−6.9	2.39	−2.6	2.55	3.9
0.75	2.36	2.17	−7.9	2.30	−2.5	2.55	8.1
0.90	1.65	1.35	−17.8	1.48	−10.2	1.76	6.7

Percentage differences are computed relative to the CLF5605 reference airfoil.

Table 4 Airfoil thickness comparison at selected chord fractions

x/c	Roamx-0201		Roamx-0201-us-f		Roamx-0201-us-pl		Roamx-0201-jp-fp	
	mm		mm	Δ , %	mm	Δ , %	mm	Δ , %
0.10	0.41		0.93	129.5	0.98	140.2	0.29	-28.6
0.25	0.50		1.04	107.0	1.09	118.8	0.40	-20.8
0.50	0.50		1.05	110.0	1.08	115.2	0.48	-4.8
0.75	0.50		1.09	117.1	1.08	116.5	0.54	8.7
0.90	0.41		0.98	140.8	0.96	135.7	0.50	22.7

Percentage differences are computed relative to the roamx-0201 reference airfoil.

Table 5 Camber line height at selected chord fractions

x/c	Roamx0201		Roamx0201-us-f		Roamx0201-us-pl		Roamx0201-jp-fp	
	mm		mm	Δ , %	mm	Δ , %	mm	Δ , %
0.10	0.73		0.80	10.3	0.87	19.4	0.83	13.6
0.25	1.58		1.61	1.9	1.75	11.0	1.66	5.2
0.50	2.26		1.98	-12.3	2.12	-6.1	2.03	-10.3
0.75	1.84		1.38	-25.0	1.45	-20.8	1.40	-23.6
0.90	0.93		0.62	-33.4	0.61	-34.6	0.65	-30.4

Percentage differences are computed relative to the roamx-0201 reference airfoil.




Fig. 22 $\bar{C}_L$ vs α (top row), $\bar{C}_L/\bar{C}_D$ vs α (middle row), and $\bar{C}_L$ vs $\bar{C}_D$ polars (bottom row) for CLF5605 and roamx-2021 airfoils obtained using 3D-SP simulations and MWT experiments.

Table 6 Summary of comparison between CLF5605 and roamx-0201 airfoils

Metric	Airfoil	3D-SP OVERFLOW	3D-SP PyFR	MWT experiments (us/jp)
Max $\bar{C}_L$	CLF5605	1.062	1.069	0.770/0.854
	Roamx-0201	1.296	1.281	0.861/0.622
Improvement in max $\bar{C}_L$	—	+22.1%	+19.8%	+11.8% / -27.2%
α at max $\bar{C}_L$	CLF5605	5.0 deg	5.0 deg	6.0 deg/6.0 deg
	Roamx-0201	6.0 deg	6.0 deg	6.0 deg/6.0 deg
Max $\bar{C}_L/\bar{C}_D$	CLF5605	18.65	18.27	8.51/8.52
	Roamx-0201	26.38	26.11	12.20/10.13
Improvement in max $\bar{C}_L/\bar{C}_D$	—	+41.5%	+42.9%	+32.3% / +18.9%
α at max $\bar{C}_L/\bar{C}_D$	CLF5605	2.0 deg	2.0 deg	4.0 deg/4.0 deg
	Roamx-0201	4.5 deg	4.5 deg	5.0 deg/6.0 deg
Stall observed	CLF5605	Yes ($\alpha > 5$ deg)	Yes ($\alpha > 5$ deg)	No/no
	Roamx-0201	No	No	No/no
Lift increment observed	CLF5605	No	No	No/no
	Roamx-0201	Yes ($\alpha > 4.0$ deg)	Yes ($\alpha > 4.0$ deg)	Yes ($\alpha > 4.0$ deg)/no

For the MWT experiments, values are reported as a range across the two tested models (us and jp). Percentages are computed as relative differences with respect to CLF5605.

Across methodologies, the roamx-0201 airfoil consistently achieves higher aerodynamic efficiency. Specifically, in 3D-SP simulations, the maximum $\bar{C}_L/\bar{C}_D$ increases by 41.5% (OVERFLOW) and 42.9% (PyFR) relative to CLF5605. MWT experiments show improvements ranging from 18.9% to 32.3%, depending on the tested model. The angle at which maximum efficiency occurs is also shifted to higher α for the roamx-0201 airfoil, indicating a broader useful operating range.

While both airfoils achieve a linear lift slope for a range of α , their postlinear behavior diverges significantly. Specifically, 3D-SP simulations show that the CLF5605 airfoil stalls when $\alpha > 5$ deg. However, in contrast, 3D-SP simulations and MWT experiments show that the roamx-0201 airfoil achieves an increment in lift when $\alpha > 4$ deg due to separation from the sharp leading edge followed by a Kelvin–Helmholtz instability and subsequent roll-up of vortices close to the upper surface of the airfoil, resulting in a recirculation region in a time-averaged sense adjacent to the front half of the upper surface that sustains suction over a significant portion of the airfoil. Consequently, in 3D-SP simulations, the roamx-0201 airfoil can achieve a maximum $\bar{C}_L$ 19.8–22.1% higher than the CLF5605 airfoil.

V. Future Work

Future work should look to further understand remaining discrepancies between the VWT PyFR and MWT experimental results. Specifically, further VWT PyFR simulations that incorporate scanned model geometries, surface roughness representations, and a range of turbulent inlet conditions could be undertaken. Future work should also examine sensitivity to Reynolds number, Mach number, and angle of attack, since Martian rotor blades operate over a wide range of local Reynolds and Mach numbers due to variations in rotational speed and chord along their span, and blade twist introduces spanwise variation in angle of attack. Changes in Reynolds number may alter separation location and vortex coherence, while changes in Mach number may modify pressure gradients and the strength of the separated shear layer. Finally, future work should assess the effectiveness of the roamx-0201 lift generation mechanism under dynamic pitch, including potential hysteresis effects.

VI. Conclusions

This study compares the aerodynamic performance of the CLF5605 rotor airfoil—which flew on Ingenuity in 2021—with that of a new optimized roamx-0201 airfoil designed for Martian conditions at NASA Ames Research Center. Specifically, performance was studied at a chord-based Reynolds number of 20,000 and a Mach number of 0.60 across a range of angles of attack. In this regime, flow can be highly sensitive to geometry and operating

conditions, and results from both computational analysis and physical testing can be strongly affected by small differences in setup. Accordingly, in order to achieve confidence in observed performance trends, the airfoils were studied using three independent state-of-the-art methodologies: ILES using NASA's OVERFLOW solver, DNS using the high-order GPU-accelerated PyFR solver, and experimental testing in the MWT at Tohoku University. Discrepancies between results obtained using the various methodologies were identified and discussed, including disagreement between the 2D and 3D-SP simulation results, between the 3D-SP simulation results and the MWT experimental results, and between the various MWT experimental results. However, across methodologies, the roamx-0201 airfoil achieves an ~19–43% improvement in lift-to-drag ratio relative to the CLF5605 airfoil. Moreover, 3D-SP simulations show that the roamx-0201 airfoil has superior stall characteristics and can achieve a maximum lift ~20% higher than the CLF5605 airfoil. The work provides a strong body of evidence to support further studies into the use of rotors based on the optimized roamx-0201 airfoil for future Mars helicopters, with the potential to deliver increased range, flight duration, and payload compared to Ingenuity. Such capabilities would allow next-generation vehicles to explore further and faster and to carry scientific instruments and/or surface samples, enabling a wider set of Mars science and discovery missions.

Appendix A: Mesh Independence Study (OVERFLOW and PyFR)

Figure A1 shows absolute percentage differences in time-averaged lift and drag coefficients with respect to the finest mesh, $|\Delta\bar{C}_L|\%$ and $|\Delta\bar{C}_D|\%$, plotted as a function of the number of elements N_e to assess mesh convergence for 2D OVERFLOW and 2D PyFR simulations of CLF5605 and roamx-0201 at $\alpha = 6$ deg.

The absolute percentage differences in time-averaged lift and drag coefficients are defined as

$$|\Delta\bar{C}_L|\% = \left| \frac{\bar{C}_L^{(i)} - \bar{C}_L^{(\text{fine})}}{\bar{C}_L^{(\text{fine})}} \right| \times 100\% \quad \text{and} \quad |\Delta\bar{C}_D|\% = \left| \frac{\bar{C}_D^{(i)} - \bar{C}_D^{(\text{fine})}}{\bar{C}_D^{(\text{fine})}} \right| \times 100\% \quad (\text{A1})$$

respectively, where $\bar{C}_L^{(i)}$ and $\bar{C}_D^{(i)}$ denote values obtained on mesh i , and $\bar{C}_L^{(\text{fine})}$ and $\bar{C}_D^{(\text{fine})}$ refer to the values obtained from the finest mesh. For both OVERFLOW and PyFR, the 2D meshes for which both $|\Delta\bar{C}_L|\%$ and $|\Delta\bar{C}_D|\%$ were below 1% were used for all simulations, corresponding to the second-finest mesh tested.




Fig. A1 Absolute percentage differences in time-averaged lift and drag coefficients with respect to the finest mesh, $|\Delta \bar{C}_L|$ % and $|\Delta \bar{C}_D|$ %, plotted as a function of the number of grid points N_{gp} for 2D OVERFLOW and number of elements N_e for 2D PyFR to assess grid convergence of CLF5605 and roamx-0201 at $\alpha = 6$.

Appendix B: Domain Span Independence Study (OVERFLOW and PyFR)

Figure B1 shows plots of $\bar{C}_p$ on both upper and lower surfaces of the CLF5605 and roamx-0201 airfoils at $\alpha = 6$ deg as a function of

$\tilde{x} = x/a$ for 3D-SP OVERFLOW and 3D-SP PyFR with different domain spans $d_z = 0.25, 0.5$ and 0.75 chord lengths. Figure B2 shows the absolute percentage differences in $\bar{C}_L$ and $\bar{C}_D$ with respect to the largest spanwise domain, $d_z = 0.75$. For both OVERFLOW




Fig. B1 Plots of time-averaged pressure coefficient $\bar{C}_p$ as a function of $\tilde{x}$ for different span lengths of the domain d_z to assess domain span length independence for 3D-SP OVERFLOW and PyFR simulations of CLF5605 and roamx-0201 at $\alpha = 6$ deg.




Fig. B2 Absolute percentage differences in time-averaged lift and drag coefficients with respect to the largest spanwise extent of the domain $d_z = 0.75$, $|\Delta \bar{C}_L| \%$, and $|\Delta \bar{C}_D| \%$, plotted as a function of d_z for 3D-SP OVERFLOW and 3D-SP PyFR to assess the required spanwise extent of the domain for CLF5605 and roamx-0201 at $\alpha = 6$ deg.




Fig. B3 Images of instantaneous density gradient magnitude $|\nabla \rho|$ in the y - z plane at a distance of 0.05 chord lengths from the trailing edge for 3D-SP PyFR on CLF5605 (left) and roamx-0201 (right) at $\alpha = 6$ deg with domain span lengths of $d_z = 0.25$, $d_z = 0.5$, and $d_z = 0.75$ chord lengths. Note that for $d_z = 0.25$ and $d_z = 0.5$ chord lengths the periodic data are repeated 3 and 1.5 times, respectively, to facilitate comparison.

and PyFR, the differences decrease as d_z increases, with variation below 1% in most cases for $d_z = 0.5$, except for the CLF5605 airfoil with PyFR, which varied by $\sim 3.8\%$.

To complement this analysis, Fig. B3 presents instantaneous density-gradient magnitude fields in the y - z plane for different domain spans. For $d_z = 0.25$, the flow exhibits artificially repeated

spanwise structures due to the imposed periodicity. As the spanwise extent increases from $d_z = 0.25$ to $d_z = 0.5$, these structures become less correlated and are allowed to naturally break down.

Based on these results, a domain span of $d_z = 0.5$ chord lengths was employed here.

Appendix C: DNS Resolution Study (PyFR)

Figures C3 and C4 show plots of Δ/η along various midspan lines for 3D-SP PyFR simulations at $\alpha = 6$ deg for CLF5605 and roamx-0201, where Δ is an estimate of the solution point spacing given by Eq. (7) and η is an estimate of the Kolmogorov length scale

given by Eq. (8). It is shown that $3.5\eta > \Delta$ in the wake for 6 chords downstream of the airfoil. This is consistent with ranges reported in prior DNS studies [35,36]. Specifically, Buxton et al. [35] examined the relationship between η and spatial resolution by filtering DNS data of a nominally two-dimensional planar mixing layer onto meshes ranging from 2.5η to 15η , showing that the required resolution depends on the statistics of interest, with $2.5\eta - 5\eta$ providing good agreement with experimental data. Similarly, Laizet et al. [36] compared simulations of grid-generated turbulence at resolutions up to 2η , 4η , and 7η against experimental measurements, reporting that a resolution of approximately 5η was sufficient to reproduce first- and second-order statistics within a small margin.




Fig. C1 Plots of Δ/η in the midspan plane as a function of y at $x = 1$, $x = 3$, and $x = 6$ for 3D-SP PyFR at $\alpha = 6$ deg.




Fig. C2 Plots of Δ/η in the midspan plane as a function of x at $y = 0.05$ and $y = -0.2$ for 3D-SP PyFR at $\alpha = 6$ deg.




Fig. C3 Plots of Δ/η in the midspan plane as a function of y at $x = 1$, $x = 3$, and $x = 6$ for 3D-SP PyFR at $\alpha = 6$ deg.




Fig. C4 Plots of Δ/η in the midspan plane as a function of x at $y = 0.05$, and $y = -0.2$ for 3D-SP PyFR at $\alpha = 6$ deg.

Appendix D: Surface Pressure for All α

Figure D1 shows plots of $\bar{C}_p$ on both upper and lower surfaces of the CLF5605 airfoil as a function of $\tilde{x} = x/a$, where a is the x -wise distance between the leading and trailing edges of the airfoil, for all tested α . Results are shown for 2D OVERFLOW, 2D PyFR, 3D-SP

OVERFLOW, 3D-SP PyFR, and MWT PSP experiments on model clf5605-us-fp.

Figure D2 shows plots of $\bar{C}_p$ on both upper and lower surfaces of the roamx-0201 airfoil as a function of $\tilde{x} = x/a$, where a is the x -wise distance between the leading and trailing edges of the airfoil,




Fig. D1 Plots of time-averaged pressure coefficient $\bar{C}_p$ as a function of $\tilde{x}$ for different angles of attack α for the CLF5605 airfoil.




Fig. D2 Plots of time-averaged pressure coefficient $\bar{C}_P$ as a function of $\tilde{x}$ for different angles of attack α for the roamx-0201 airfoil.

for all tested α . Results are shown for 2D OVERFLOW, 2D PyFR, 3D-SP OVERFLOW, 3D-SP PyFR, VWT PyFR, and MWT PSP experiments on models roamx-0201-us-pu, roamx-0201-us-pl, and roamx-0201-jp-fpu.

Appendix E: Schlieren and Instantaneous Density Gradient for All α

Figure E1 shows schlieren images for MWT experiments on model clf5605-us-s (left) and images of instantaneous density gradient magnitude $|\nabla\rho|$ for 3D-SP OVERFLOW (middle) and PyFR (right) on CLF5605 at all tested α .

Figure E2 shows schlieren images for MWT experiments on model roamx-0201-jp-s (left) and images of instantaneous density gradient magnitude $|\nabla\rho|$ for 3D-SP OVERFLOW (middle) and PyFR (right) on roamx-0201 at all tested α .

Acknowledgments

This paper is dedicated to the memory of Keisuke Asai, who sadly passed away on August 11, 2025. Resources supporting this work were provided by the NASA High-End Computing (HEC) Program through the NASA Advanced Supercomputing (NAS) Division at Ames Research Center. The authors are grateful for support from the Engineering and Physical Sciences Research Council via an EPSRC Fellowship (EP/R030340/1) and for compute allocation on Piz Daint and Alps at the Swiss National Supercomputing Centre (CSCS). The authors gratefully acknowledge the outstanding support of Miku Kasai, Yudai Kanzaki, and Muku Miyagi in conducting the MWT experimental work. The authors also wish to express their sincere appreciation to Jordan Farrar for the careful scanning of the airfoil models and to Ashley Tan for postprocessing of the scanned data. The authors also thank Jon-Pierre Wiens and Charles Cornelison for the professional photography of the airfoil models.




Fig. E1 Schlieren images for MWT experiments on model clf5605-us-s (left) and images of instantaneous density gradient magnitude $|\nabla\rho|$ for 3D-SP OVERFLOW (middle) and PyFR (right) on CLF5605 for different α .




Fig. E2 Schlieren images for MWT experiments on model roamx-0201-jp-s (left) and images of instantaneous density gradient magnitude $|\nabla\rho|$ for 3D-SP OVERFLOW (middle) and PyFR (right) on roamx-0201 for different α .

References

- [1] Balaram, J. B., Canham, T., Duncan, C., Golombek, M., Grip, H. F., Johnson, W., Maki, J., Quon, A., Stern, R., and Zhu, D., "Mars Helicopter Technology Demonstrator," *AIAA Atmospheric Flight Mechanics Conference*, AIAA Paper 2018-0023, 2018. <https://doi.org/10.2514/6.2018-0023>
- [2] Johnson, W., Withrow-Maser, S., Young, L., Malpica, C., Koning, W. J. F., Kuang, W., Fehler, M., Tuano, A., Chan, A., Datta, A., et al., "Mars Science Helicopter Conceptual Design," NASA TM 2020-220485, March 2020, <https://ntrs.nasa.gov/citations/20200002139>.
- [3] Withrow-Maser, S., Johnson, W., Schatzman, N., Young, L., Cummings, H., Malpica, C., Meyn, L., Allan, B., Tzanetos, T., Grip, H., et al., "Mars Sample Recovery Helicopter: Rotorcraft to Retrieve the First Samples from the Martian Surface," *Vertical Flight Society 79th Annual Forum & Technology Display*, Vertical Flight Soc. Paper 17969, Fairfax, VA, 2023. <https://doi.org/10.4050/F-0079-2023-17969>
- [4] Withrow-Maser, S., Johnson, W., Koning, W. J. F., Ågren, T., Sahragard-Monfared, G., Bowman, J., Kaweesa, D., Ruan, A., Malpica, C., Jones-Wilson, L., et al., "Critical Aerodynamic and Performance Upgrades to Enable Larger Mars Rotorcraft Such as the Chopper Platform," *Vertical Flight Society 81st Annual Forum & Technology Display*, Vertical Flight Soc. Paper 388, Fairfax, VA, May 2025. <https://doi.org/10.4050/F-0081-2025-388>

- [5] Koning, W. J. F., Johnson, W., and Grip, H. F., "Improved Mars Helicopter Aerodynamic Rotor Model for Comprehensive Analyses," *AIAA Journal*, Vol. 57, No. 9, 2019, pp. 3969–3979. <https://doi.org/10.2514/1.J058045>
- [6] Koning, W. J. F., Romander, E. A., and Johnson, W., "Low Reynolds Number Airfoil Evaluation for the Mars Helicopter Rotor," ARC-E-DAA-TN50660, 2018, <https://ntrs.nasa.gov/citations/20180008702>.
- [7] Koning, W. J. F., "Airfoil Selection for Mars Rotor Applications," NASA CR 2019-220236, 2019, <https://ntrs.nasa.gov/citations/20190031929>.
- [8] Koning, W. J. F., Perez, B. N., Cummings, H. V., Romander, E. A., and Johnson, W., "ELISA: A Tool for Optimization of Rotor Hover Performance at Low Reynolds Number in the Mars Atmosphere," *Journal of the American Helicopter Society*, Vol. 69, No. 4, 2024, Paper 042005. <https://doi.org/10.4050/JAHS.69.042005>
- [9] Herrero, A. G., Noguchi, A., Kusama, K., Shigeta, T., Nagata, T., Nonomura, T., and Asai, K., "Effects of Compressibility and Reynolds Number on the Aerodynamics of a Simplified Corrugated Airfoil," *Experiments in Fluids*, Vol. 62, No. 4, 2021, pp. 1–20. <https://doi.org/10.1007/s00348-021-03164-0>
- [10] Okamoto, M., Yasuda, K., and Azuma, A., "Aerodynamic Characteristics of the Wings and Body of a Dragonfly," *Journal of Experimental Biology*, Vol. 199, No. 2, 1996, pp. 281–294. <https://doi.org/10.1242/jeb.199.2.281>
- [11] Suwa, T., Nose, K., Numata, D., Nagai, H., and Asai, K., "Compressibility Effects on Airfoil Aerodynamics at Low Reynolds Number," *30th AIAA Applied Aerodynamics Conference*, AIAA Paper 2012-3029, Reston, VA, 2012. <https://doi.org/10.2514/6.2012-3029>
- [12] Munday, P., Taira, K., Suwa, T., Numata, D., and Asai, K., "Non-Linear Lift on a Triangular Airfoil in Low-Reynolds-Number Compressible Flow," *Journal of Aircraft*, Vol. 52, No. 3, 2015, pp. 924–931. <https://doi.org/10.2514/1.C032983>
- [13] Caros, L., Buxton, O., Shigeta, T., Nagata, T., Nonomura, T., Asai, K., and Vincent, P., "Direct Numerical Simulation of Flow over a Triangular Airfoil Under Martian Conditions," *AIAA Journal*, Vol. 60, No. 9, 2022, pp. 5531–5546. <https://doi.org/10.2514/1.J061454>
- [14] Caros, L., Buxton, O., and Vincent, P., "Optimization of Triangular Airfoils for Martian Helicopters Using Direct Numerical Simulations," *AIAA Journal*, Vol. 62, No. 5, 2024, pp. 2603–2616. <https://doi.org/10.2514/1.J063164>
- [15] Caros, L., Buxton, O., and Vincent, P., "Effects of Freestream Eddies on Triangular Airfoils for Martian Rotorcraft," *AIAA Journal*, Vol. 63, No. 9, 2025, pp. 3719–3736. <https://doi.org/10.2514/1.J065427>
- [16] Koning, W. J. F., Romander, E. A., and Johnson, W., "Optimization of Low Reynolds Number Airfoils for Martian Rotor Applications Using an Evolutionary Algorithm," *AIAA SciTech 2020 Forum*, AIAA Paper 2020-0084, 2020. <https://doi.org/10.2514/6.2020-0084>
- [17] Koning, W. J. F., Perez, B. N., Dominguez, M., and Cummings, H., "ROAMX Rotor Geometry," NASA TM 20250006640, 2025, <https://ntrs.nasa.gov/citations/20250006640>.
- [18] Cummings, H., Perez, B. N. P., Koning, W. J. F., Johnson, W., Young, L., Haddad, F., Romander, E., Balam, J. B., Tzanetos, T., Bowman, J., et al., "Overview and Introduction of the Rotor Optimization for the Advancement of Mars eXploration (ROAMX) Project," *Meeting: Aeromechanics for Advanced Vertical Flight Technical Meeting, Transformative Vertical Flight 2022*, Vertical Flight Soc. Paper 17269, Fairfax, VA, 2022, <https://ntrs.nasa.gov/citations/20210026440>.
- [19] Pipenberg, B. T., Keennon, M., Tyler, J., Hibbs, B., Langberg, S., Balam, J. B., Grip, H. F., and Pempejian, J., "Design and Fabrication of the Mars Helicopter Rotor, Airframe, and Landing Gear Systems," *AIAA SciTech 2019 Forum*, AIAA Paper 2019-0620, 2019. <https://doi.org/10.2514/6.2019-0620>
- [20] Koning, W. J. F., and Dominguez, M., "Mars Helicopter Ingenuity Rotor Geometry," NASA TM 20240001510, 2024, <https://ntrs.nasa.gov/citations/20240001510>.
- [21] Koning, W. J. F., Dominguez, M., and Johnson, W., "Mars Science Helicopter Rotor Geometry," NASA TM 20240013701, Nov. 2024, https://rotorcraft.arc.nasa.gov/Publications/files/Koning_NF20250203.pdf.
- [22] Nichols, R. H., and Buning, P. G., *User's Manual for OVERFLOW 2.2o*, NASA Langley Research Center, Hampton, VA, March 2021.
- [23] Pulliam, T., "High Order Accurate Finite-Difference Methods: As Seen in OverFlow," *20th AIAA Computational Fluid Dynamics Conference*, AIAA Paper 2011-3851, 2011. <https://doi.org/10.2514/6.2011-3851>
- [24] Witherden, F. D., Farrington, A. M., and Vincent, P. E., "PyFR: An Open Source Framework for Solving Advection–Diffusion Type Problems on Streaming Architectures Using the Flux Reconstruction Approach," *Computer Physics Communications*, Vol. 185, No. 11, 2014, pp. 3028–3040. <https://doi.org/10.1016/j.cpc.2014.07.011>
- [25] Witherden, F. D., Vincent, P. E., Trojak, W., Abe, Y., Akbarzadeh, A., Akkurt, S., Alhawary, M., Caros, L., Dzanic, T., Giangaspero, G., et al., "PyFR v2.0.3: Towards Industrial Adoption of Scale-Resolving Simulations," *Computer Physics Communications*, Vol. 311, June 2025, Paper 109567. <https://doi.org/10.1016/j.cpc.2025.109567>
- [26] Anyoji, M., Nose, K., Ida, S., Numata, D., Nagai, H., and Asai, K., "Development of a Low-Density Wind Tunnel for Simulating Martian Atmospheric Flight," *Transactions of the Japanese Society for Artificial Intelligence, Aerospace Technology Japan*, Vol. 9, 2011, pp. 21–27. <https://doi.org/10.2322/tastj.9.21>
- [27] Nichols, R. H., Tramel, R. W., and Buning, P. G., "Evaluation of Two High-Order Weighted Essentially Nonoscillatory Schemes," *AIAA Journal*, Vol. 46, No. 12, 2008, pp. 3090–3102. <https://doi.org/10.2514/1.36849>
- [28] Pulliam, T., "Time Accuracy and the Use of Implicit Methods," *11th Computational Fluid Dynamics Conference*, AIAA Paper 1993-3360, 2012. <https://doi.org/10.2514/6.1993-3360>
- [29] Venkateswaran, S., and Merkle, C., "Dual Time-Stepping and Preconditioning for Unsteady Computations," *33rd Aerospace Sciences Meeting and Exhibit*, AIAA Paper 1995-0078, 2012. <https://doi.org/10.2514/6.1995-78>
- [30] Huynh, H. T., "A Reconstruction Approach to High-Order Schemes Including Discontinuous Galerkin for Diffusion," *47th AIAA Aerospace Sciences Meeting Including the New Horizons Forum and Aerospace Exposition*, AIAA Paper 2009-0403, 2009. <https://doi.org/10.2514/6.2009-403>
- [31] Kennedy, C. A., Carpenter, M. H., and Lewis, R. M., "Low-Storage, Explicit Runge–Kutta Schemes for the Compressible Navier–Stokes Equations," *Applied Numerical Mathematics*, Vol. 35, No. 3, 2000, pp. 177–219. [https://doi.org/10.1016/S0168-9274\(99\)00141-5](https://doi.org/10.1016/S0168-9274(99)00141-5)
- [32] Koning, W. J. F., Romander, E. A., Cummings, H. V., Perez, B. N., and Buning, P. G., "On Improved Understanding of Airfoil Performance Evaluation Methods at Low Reynolds Numbers," *Journal of Aircraft*, Vol. 60, No. 3, 2023, pp. 774–788. <https://doi.org/10.2514/1.C037023>
- [33] Koning, W. J. F., Allan, B. G., Romander, E. A., and Johnson, W., "Comparing 3D and 2D CFD for Mars Helicopter Ingenuity Rotor Performance Prediction," *49th European Rotorcraft Forum (ERF)*, Deutsche Gesellschaft für Luft- und Raumfahrt (DGLR) Document ID: 54801024, Bonn, Germany, Sept. 2023, https://rotorcraft.arc.nasa.gov/Publications/files/Comparing_3D_and_2D_CFD_for_Mars.pdf.
- [34] Bergmann, M., Morsbach, C., Ashcroft, G., and Kugeler, E., "Statistical Error Estimation Methods for Engineering-Relevant Quantities from Scale-Resolving Simulations," *Journal of Turbomachinery*, Vol. 144, No. 3, 2022, Paper 031007. <https://doi.org/10.1115/1.4052402>
- [35] Buxton, O., Laizet, S., and Ganapathisubramani, B., "The Effects of Resolution and Noise on Kinematic Features of Fine-Scale Turbulence," *Experiments in Fluids*, Vol. 51, No. 5, 2011, pp. 1417–1437. <https://doi.org/10.1007/s00348-011-1159-2>
- [36] Laizet, S., Nedić, J., and Vassilicos, C., "Influence of the Spatial Resolution on Fine-Scale Features in DNS of Turbulence Generated by a Single Square Grid," *International Journal of Computational Fluid Dynamics*, Vol. 29, Nos. 3–5, 2015, pp. 286–302. <https://doi.org/10.1080/10618562.2015.1058371>
- [37] Anyoji, M., "Development of a Mars Wind Tunnel and Its Applications to Low Reynolds Number and High-Subsonic Airfoil Testing," Ph.D. Thesis, Tohoku Univ., Sendai, Japan, 2011.
- [38] Anyoji, M., Numata, D., Nagai, H., and Asai, K., "Supersonic Ejector-Driving System Under Low Pressure: A Performance Evaluation," *Transactions of the Japan Society for Aeronautical and Space Sciences*, Vol. 64, No. 3, 2021, pp. 156–164. <https://doi.org/10.2322/tjsass.64.156>
- [39] Anyoji, M., Numata, D., Nagai, H., and Asai, K., "Effects of Mach Number and Specific Heat Ratio on Low-Reynolds-Number Airfoil Flows," *AIAA Journal*, Vol. 53, No. 6, 2015, pp. 1640–1654. <https://doi.org/10.2514/1.J053468>
- [40] Nagata, T., Nonomura, T., Kanzaki, Y., Nagatsuka, A., and Asai, K., "Compressible Flow over NACA 4-Digit Airfoils with Different

- Thickness at $Re=10,000$,” *AIAA Journal*, Feb. 2026.
<https://doi.org/10.2514/1.J065645>
- [41] Mangeol, E., Ishiwaki, D., Wallisky, N., Asai, K., and Nonomura, T., “Compressibility Effects on Flat-Plates with Serrated Leading-Edges at a Low Reynolds Number,” *Experiments in Fluids*, Vol. 58, No. 11, 2017, pp. 1–15.
<https://doi.org/10.1007/s00348-017-2443-6>
- [42] Kusama, K., Nagata, T., Anyoji, M., Nonomura, T., and Asai, K., “Investigation of Mach Number Effects on Flow over a Flat Plate at Reynolds Number of 1.0×10^4 by Schlieren Visualization,” *Fluid Dynamics Research*, Vol. 53, No. 1, 2021, Paper 015513.
<https://doi.org/10.1088/1873-7005/abe04c>
- [43] Nagata, T., Noguchi, A., Kusama, K., Nonomura, T., Komuro, A., Ando, A., and Asai, K., “Experimental Investigation on Compressible Flow over a Circular Cylinder at Reynolds Number of Between 1000 and 5000,” *Journal of Fluid Mechanics*, Vol. 893, June 2020, Paper A13.
<https://doi.org/10.1017/jfm.2020.221>
- [44] Nagata, T., Shigeta, T., Kasai, M., and Nonomura, T., “Schlieren Visualization and Drag Measurement on Compressible Flow over a Circular Cylinder at Reynolds Number of $O(10^2)$,” *Experiments in Fluids*, Vol. 66, No. 5, 2025, p. 91.
<https://doi.org/10.1007/s00348-025-04010-3>
- [45] Nagata, T., Sato, H., Okochi, M., Matsuyama, T., Sugioka, Y., Kasai, M., Kusama, K., Numata, D., Nonomura, T., and Asai, K., “Visualization of Pressure and Skin-Friction Fields on Rotating Blade Under Low-Pressure Conditions,” *AIAA Journal*, Vol. 60, No. 9, 2022, pp. 5422–5435.
<https://doi.org/10.2514/1.J061638>
- [46] Koning, W. J. F., Perez, N. P., Cummings, H. V., Nagata, T., Kanzaki, Y., Kasai, M., Miyagi, M., Nonomura, T., Asai, K., Caros, L., et al., “Experimental Results for Mars Rotorcraft Airfoils (Roamx-0201 and clf5605) at Low Reynolds Number and Compressible Flow in a Mars Wind Tunnel,” NASA TM 20240004230, 2024, <https://ntrs.nasa.gov/citations/20240004230>.
- [47] Liu, T., Sullivan, J. P., Asai, K., Klein, C., and Egami, Y., *Pressure and Temperature Sensitive Paints*, 2nd ed., Springer, Berlin, 2021, pp. 31–72, Chap. 3.
- [48] Nagata, T., Kasai, M., Okudera, T., Sato, H., Nonomura, T., and Asai, K., “Optimum Pressure Range Evaluation toward Aerodynamic Measurements Using PSP in Low-Pressure Conditions,” *Measurement Science and Technology*, Vol. 31, No. 8, 2020, Paper 085303.
<https://doi.org/10.1088/1361-6501/ab81bb>
- [49] Kasai, M., Sasaki, D., Nagata, T., Nonomura, T., and Asai, K., “Frequency Response of Pressure-Sensitive Paints Under Low-Pressure Conditions,” *Sensors*, Vol. 21, No. 9, 2021, p. 3187.
<https://doi.org/10.3390/s21093187>
- [50] Kasai, M., Nagata, T., and Nonomura, T., “Indexes for Evaluation of Dynamic Characteristics of Pressure-Sensitive Paint Based on Pressure Sensitivity and Frequency Response,” *Measurement Science and Technology*, Vol. 35, No. 6, 2024, Paper 065101.
<https://doi.org/10.1088/1361-6501/ad2b41>
- [51] Nagai, K., Masuda, T., Nakagawa, T., Freeman, B. D., and Pinnau, I., “Poly [1-(trimethylsilyl)-1-Propyne] and Related Polymers: Synthesis, Properties and Functions,” *Progress in Polymer Science*, Vol. 26, No. 5, 2001, pp. 721–798.
[https://doi.org/10.1016/S0079-6700\(01\)00008-9](https://doi.org/10.1016/S0079-6700(01)00008-9)
- [52] Mori, H., Niimi, T., Hirako, M., and Uenishi, H., “Pressure Sensitive Paint Suitable to High Knudsen Number Regime,” *Measurement Science and Technology*, Vol. 17, No. 6, 2006, pp. 1242–1246.
<https://doi.org/10.1088/0957-0233/17/6/S02>
- [53] Anyoji, M., Numata, D., Nagai, H., and Asai, K., “Pressure-Sensitive Paint Technique for Surface Pressure Measurements in a Low-Density Wind Tunnel,” *Journal of Visualization*, Vol. 18, No. 2, 2014, pp. 297–309.
<https://doi.org/10.1007/s12650-014-0239-9>
- [54] Sugioka, Y., Numata, D., Asai, K., Koike, S., Nakakita, K., and Nakajima, T., “Polymer/Ceramic Pressure-Sensitive Paint with Reduced Roughness for Unsteady Measurement in Transonic Flow,” *AIAA Journal*, Vol. 56, No. 6, 2018, pp. 2145–2156.
<https://doi.org/10.2514/1.J056304>
- [55] Kasai, M., Nagata, T., Uchida, K., Nonomura, T., Asai, K., and Egami, Y., “Evaluation of Characteristics of Fast-Response Pressure-Sensitive Paint Under Low-Pressure Conditions,” *Measurement Science and Technology*, Vol. 34, No. 7, 2023, Paper 075103.
<https://doi.org/10.1088/1361-6501/acc5a0>
- [56] Anyoji, M., Numata, D., Nagai, H., and Asai, K., “Pressure-Sensitive Paint Technique for Surface Pressure Measurements in a Low-Density Wind Tunnel,” *Journal of Visualization*, Vol. 18, No. 2, 2015, pp. 297–309.
<https://doi.org/10.1007/s12650-014-0239-9>

P. G. Tucker
 Associate Editor